


BUDD-CAST®
NYLON
ELEVATOR BUCKET



TECHNICAL SPECIFICATION - BUDD-CAST® NYLON ELEVATOR BUCKET

Type	A	B	H1	T	 Nylon	Capacity (W-L)	Capacity (X-Y)	Holes	D	E	I
Dimensions	mm	mm	mm	mm	kgs.	Ltr.	Ltr.	No.	mm	mm	mm
BUDD AA064 CN	164	103	110	4,8	0,5	0,51	0,79	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA085 CN	214	127	140	6,4	1,16	1,05	1,62	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA093 CN	243	84	87	6,4	0,28	0,25	0,68	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA106 CN	268	154	159	7,1	1,92	1,86	2,88	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA127 CN	315	191	186	9,5	2,79	3,21	4,42	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA147 CN	374	193	188	9,5	3,6	3,96	6,12	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA148 CN	369		215	9,5	4,83	4,58	7,25	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA155 CN	400	138	145	11,1	2,2	2,29	3,43	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA168 CN	422	204	217	12,7	5,73	5,38	8,22	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA188 CN	451	204	215	12,7	5,98	8,75	5,95	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA1810 CN	478	259	268	12,7	7,16	13,76	8,84	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA195 CN	505	133	131	11,1	2,36	3,74	2,41	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA248 CN	611	220	220	14,2	7,16	10,23	7,31	cust. spec.	cust. spec.	cust. spec.	cust. spec.
BUDD AA2413 CN	610	323	323	19,0	14,65	28,32	15,52	cust. spec.	cust. spec.	cust. spec.	cust. spec.

- Type BUDD-CAST® elevator bucket has flat holes in the back of the bucket and on the inside of the bucket and needs to be fitted on the elevator belt by using a DIN15237 elevator bolt in combination with a flat washer according to DIN9021 (Fig.1). Contact a Muller Beltex representative for advice on the recommended bolt hole pattern.

- Only available in nylon, color black (max. temp +110° C.)