


PELICAN
STALEN
ELEVATORBEKER




TECHNISCHE SPECIFICATIES - PELICAN STALEN ELEVATORBEKER

Type	A	B	H1	H2	T	 Staal	Netto inhoud (W-L)	Inhoud totaal	Gaten	D	E	I	Max. bekers per meter
Maatvoering	mm	mm	mm	mm	mm	kgs.	Ltr.	Ltr.	Nr.	mm	mm	mm	Stuks
Pelican 330-250	340	260	190	130	3,0 / 4,0	4,50 / 6,00	7,20	9,60	3	13,0	80	55	5
Pelican 370-250	380	260	190	130	3,0 / 4,0	5,10 / 6,10	8,30	10,80	4	13,0	80	55	5
pelican 470-250	480	260	190	130	3,0 / 4,0 / 4,7	6,50 / 8,60 / 10,10	10,50	14,00	5	13,0	80	55	5

- Type Pelican elevatorbeker heeft gebombeerde elevatorboutgaten in de rug van de elevatorbeker en dient te worden gemonteerd op de elevatorband met een DIN15237 elevatorbout in combinatie met een holle onderlegging (Fig.1).
- Tevens in roestvrij staal of gelaste uitvoering verkrijgbaar.
- Afwijkend gatenpatroon op aanvraag.